



## K-ITM N1VVK 1000 SC

**Description :** Power flexible single core cable with PVC insulation under PVC sheath fire resistant and at low corrosive gases emission.

**Design:**



**Construction :** Flexible bare copper conductors according to CEI 20-29 Class 5 and DIN-VDE 0295 K5  
 PVC Insulation compound type **R2** according to CEI 20-11  
 Outer jacket in PVC **RZ** according to CEI 20-11

**Manufacturing's Controls:** Test and Control according to our certificated **ISO 9001-2015 CSQ-IMQ (EQ-NET)** Quality System procedure.

Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports

**Norms :**

- CEI 20-14 III° Ed. 1997
- CEI 20-22/1 - CEI 20-22/2 - CEI 20-22/4 IV° Ed. 1995
- CEI EN 50267-2-1 Ed.1999
- CEI-UNEL 35756 Ed. 1997
- CEI 20-52 I° ED.1998
- Technical Specifications IMQ-CPT 007
- The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

**Technical dates :**

- Nominal voltage : 600/1000V
- Spark Test voltage : 6000 V
- Working temperature: Occasional flexing: -5°C to +70°C  
Fixed installation: -30°C to +80°C
- Minimum bending radius 4 x OD-Ø for normal use  
2 x OD-Ø for short-term bending

**Use :** Cable for power supply and energy transmission.  
 In inner places, also wet, and outer places; fix position on brickworks and on metallic structures; possible also for under-ground laying.

Recommended for the realization of electrical systems in public places.

These cables are suitable for free not continuously movement appliance without tensile load or compulsory guidance as well as for fixed installation.