

Via D. Alighieri 33 29010 Villanova sull'Arda (PC) - Italy Tel. 0039.0523.837899 Fax 0039.0523.837381

UNI EN ISO 9001-2015 Certified Company













K-FLEX 7000 MTW UL

Description: Increased oil-resistant Control and Power supply Cables, conforming to NFPA 79 2007 wiring

norms and NEC "National Electrical Code" Art. 310, 610, 620 manufactured according to UL

1063 (MTW).

Design:



Construction: Cores construction type A according UL 1063

Flexible bare copper conductors according to CEI 20-29 Class 5, DIN-VDE 0295 K5 and UL

83 standard

Special PVC Insulation compound type QMTT2

Outer sheath in special PVC according to UL 1063

Manufacturing's

Controls:

Test and Control according to our certificated ISO 9001-2015 CSQ-IMQ (EQ-NET)

Quality System procedure.

Labor tests reports are stored in our internal Q.C. laboratory archive together with the

production reports

Norms: Flammability of Cable according category FT4/IEEE of Vertical-Tray Fire-Propagation and

Smoke-Release Test for Electrical and Optical-Fiber Cables, UL 1685 standard.

Construction according to UL 1063 (Oil-resistant according to UL OIL RES I and Water-

resistant, UL Wet Approval 75 °C)

According to CSA 239-09 Standard for Control and Instrumentation Cables

American and Canadian UL recognized aaccording to UL AWM styles 10012 and 2587 and CSA

AWM I/II A/B

The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

Technical dates: • Nominal voltage:

600 V

• Spark Test voltage: 6000 V

Fixed installation working temperature: $-40^{\circ}C$ to $+90^{\circ}C$ Occasional flexing working temperature: $-5^{\circ}C$ to $+90^{\circ}C$

• Fixed installation minimum bending radius = $4 \times \text{cable } \emptyset$

Occasional flexing minimum bending radius $= 4 \times \text{cable } \emptyset$

Use:

Efficient stocking! These control cables are especially suitable for export-orientated machinery. It is suitable for control equipment on machine tools subjected to medium mechanical stresses, for fixed or flexible installation, where free movement is required without tensile stresses and without forced guidance systems, in dry, damp and wet interiors (including water-oil mixtures). Machine tools compliant with UL MTW (Machine Tool Wiring) acc. to "National Electrical Code" Art. 310, 610, 620